# **Snap-an** Industrial Brands

## TORQUE TOOLS MECHANICAL WRENCHES

## 

### COMFORT GRIP MICROMETER ADJUSTABLE TORQUE WRENCHES - DUAL SCALE

Comfort-Grip Handle Dual Scale

#### Features

- Dual scale, calibrated dual direction
- Positive lock with spring loaded pull down lock ring
- Fast, accurate and easy to set
- Easy-to-read laser marked scale
- Most feature quick release buttons which provide good socket retention as well as easy socket removal
- Ergonomic comfort-grip
- Accuracy:  $\pm$  3% CW  $\pm$  5% CCW of indicated value, CW, from 20% to 100% of full scale
- Meets or exceeds ASME standards, ISO 6789 standards
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.



### COMFORT GRIP MICROMETER ADJUSTABLE TORQUE WRENCHES - DUAL SCALE

Drive Size	English	Incr.	Nm	Incr.	A In.	B In.	C In.	D In.
	Range		Range					
1/4"	20-150 in. lb.	1	2.8 - 15.3 Nm	.12	10.00	1.06	.93	1.06
3/8"	30-250 in. lb.	1	4.0 - 27.7 Nm	.12	11.25	1.06	1.06	1.06
3/8"	150-1000 in. lb.	5	19.8 - 110.2 Nm	.6	16.00	1.43	1.20	1.40
3/8"	10-100 ft. lb.	1	16.9 - 132.2 Nm	.7	16.00	1.43	1.20	1.40
1/2"	20-150 ft. lb.	1	34 - 197 Nm	1.4	19.00	1.70	1.40	1.40
1/2"	30-250 ft. lb.	1	47 - 332 Nm	1.4	24.40	1.70	1.40	1.40
3/4"	100-600 ft. lb.	5	169 - 779 Nm	6.8	42.00	2.50	2.10	1.40
	Size 1/4" 3/8" 3/8" 3/8" 1/2" 1/2"	Size Range   ¼" 20-150 in. lb.   ¾" 30-250 in. lb.   ¾" 150-1000 in. lb.   ¾" 10-100 ft. lb.   ½" 20-150 ft. lb.   ½" 30-250 ft. lb.	Size Range Incr.   ¼" 20-150 in. lb. 1   ¾" 30-250 in. lb. 1   ¾" 150-1000 in. lb. 5   ¾" 10-100 ft. lb. 1   ½" 20-150 ft. lb. 1   ½" 30-250 ft. lb. 1	Size Range Incr. Range   ¼" 20-150 in. lb. 1 2.8 - 15.3 Nm   ¾" 30-250 in. lb. 1 4.0 - 27.7 Nm   ¾" 150-1000 in. lb. 5 19.8 - 110.2 Nm   ¾" 10-100 ft. lb. 1 16.9 - 132.2 Nm   ½" 20-150 ft. lb. 1 34 - 197 Nm   ½" 30-250 ft. lb. 1 47 - 332 Nm	Size Range Incr. Range Incr.   ¼" 20-150 in. lb. 1 2.8 - 15.3 Nm .12   ¾" 30-250 in. lb. 1 4.0 - 27.7 Nm .12   ¾" 30-250 in. lb. 1 4.0 - 27.7 Nm .12   ¾" 150-1000 in. lb. 5 19.8 - 110.2 Nm .6   ¾" 10-100 ft. lb. 1 16.9 - 132.2 Nm .7   ½" 20-150 ft. lb. 1 34 - 197 Nm 1.4   ½" 30-250 ft. lb. 1 47 - 332 Nm 1.4	Size Range Incr. Range Incr. In.   '4" 20-150 in. lb. 1 2.8 - 15.3 Nm .12 10.00   %" 30-250 in. lb. 1 4.0 - 27.7 Nm .12 11.25   %" 150-1000 in. lb. 5 19.8 - 110.2 Nm .6 16.00   %" 10-100 ft. lb. 1 16.9 - 132.2 Nm .7 16.00   '½" 20-150 ft. lb. 1 34 - 197 Nm 1.4 19.00   '½" 30-250 ft. lb. 1 47 - 332 Nm 1.4 24.40	Size Range Incr. Range Incr. In. In.   '4" 20-150 in. lb. 1 2.8 - 15.3 Nm .12 10.00 1.06   %" 30-250 in. lb. 1 4.0 - 27.7 Nm .12 11.25 1.06   %" 150-1000 in. lb. 5 19.8 - 110.2 Nm .6 16.00 1.43   %" 10-100 ft. lb. 1 16.9 - 132.2 Nm .7 16.00 1.43   '½" 20-150 ft. lb. 1 34 - 197 Nm 1.4 19.00 1.70   '½" 30-250 ft. lb. 1 47 - 332 Nm 1.4 24.40 1.70	Size Range Incr. Range Incr. In. In. In. In.   ¼" 20-150 in. lb. 1 2.8 - 15.3 Nm .12 10.00 1.06 .93   ¾" 30-250 in. lb. 1 4.0 - 27.7 Nm .12 11.25 1.06 1.06   ¾" 150-1000 in. lb. 5 19.8 - 110.2 Nm .6 16.00 1.43 1.20   ¾" 10-100 ft. lb. 1 16.9 - 132.2 Nm .7 16.00 1.43 1.20   ½" 20-150 ft. lb. 1 34 - 197 Nm 1.4 19.00 1.70 1.40   ½" 30-250 ft. lb. 1 47 - 332 Nm 1.4 24.40 1.70 1.40



